	Model Name	K50C-SX009V	K52N-SX227V	A72JR-TY310V
EAN Code		0884840702450	0884840767657	0884840746645
Part Number		90NWPA1111113VLC633	90NZSA659A2323VL933	90NXHW621A1F41VL233
Short Commen		C220/GMA4500/DDR2 800 2G/HDD 320G 5400	P320/HD4200/DDR3 1066 4G/HDD 320G 5400	i5-460M/HD5470 1GB/DDR3 1066 4G/HDD 820G 540
3	Short Commen	RPM/Win7-HPre64bit/15.6" HD	RPM/Win7-HPre64bit/15.6" HD	RPM/Win7-HPre64bit/17.3" HD+
Display parameter		15.6" LED, 16:9 HD (1366 x 768)	15.6" CCFL, 16:9 HD (1366 x 768)	17.3" LED, 16: 9 HD+ (1600 x 900)
LCD Type		Glare (Color Shine)	Glare (Color Shine)	Glare (Color Shine)
ORU		0220.1.2011-	Athlon IIP320	2 F2CH= /Tb= t= 2 0\/2M
CPU		C220 1.2GHz	(dual core) [25W]	2.53GHz (Turbo up to 2.8)/3M
	Chipset	0	T	-
	DRAM	DDR2 800 2G	DDR3 1066 4G	DDR3 1066 4G
Memory	Expansion Up to	2G	8G	8G
	All slots	1	2	2
Intel® Turbo Memory (Robson)		N/A	N/A	N/A
Video Card		Intel GMA 4500MHD	ATI Radeon HD4200	ATI Mobility Radeon HD5470, 1GB DDR3 VRAM
	HDD	HDD 320G 5400 RPM	HDD 320G 5400 RPM	HDD 820G 5400 RPM
	ODD	Super Multi 8X with Double Layer	Super Multi 8X with Double Layer	Super Multi 8X with Double Layer
Sound		* Built-in Stereo Speakers(1.5W) and microphone * Support Audio Jack Detector for Vista Basic Logo * Support Audio CODEC criteria for Vista Premium Logo	<ul> <li>☑ Built-in Azalia compliant audio chip</li> <li>☑ Built-in 2 Stereo Speakers(2W) and microphone</li> <li>☑ Support Audio Jack Detector for Win7 Logo</li> <li>☑ Support Audio CODEC criteria for Win7 Premium</li> </ul>	<ul> <li>Altec Lansing</li> <li>SRS supported</li> <li>Built-in Azalia compliant audio chip, with 3D effect full duplex</li> </ul>
		* Altec Lancing	Logo  B Altec Lancing co-brading B SRS support	Built-in Stereo Speakers(2W) and microphone S/V Volume up/down
	Wireless LAN	802.11n	802.11n	802.11n
	BT	N/A	N/A	YES
b	ouilt-in Camera	0.3M pixel	0.3M pixel	0.3M pixel
	TV-Tuner	N/A	N/A	N/A
	Card Reader	SD / MMC / MS	SD / MMC / MS	SD / MMC / MS / MS Pro
Interfaces	USB	2 x USB 2.0	3 x USB 2.0	4 x USB 2.0
	IEEE1394	N/A	N/A	N/A
	PCMCIA / ExpressCard	N/A	N/A	N/A
	IrDA	N/A	N/A	N/A
	VGA connector	VGA-Out (D-Sub / 15pin)	VGA-Out (D-Sub / 15pin)	VGA-Out (D-Sub / 15pin)
	TV-Out	N/A	N/A	N/A
	SPDIF	N/A	N/A	N/A
	Headphone-Out	Headphone-Out	Headphone-Out	Headphone-Out
	Mic-In	Mic-In	Mic-In	Mic-In
	Line-In	N/A	N/A	N/A
	HDMI	N/A	1 x HDMI	1 x HDMI
	СОМ	-	-	-
	Modem	-	-	-
	Lan	G-Lan 10 / 100 / 1000 Mbit/s (RJ-45)	G-Lan 10 / 100 / 1000 Mbit/s (RJ-45)	G-Lan 10 / 100 / 1000 Mbit/s (RJ-45)
	E-SATA	N/A	N/A	N/A
	<b>Dock Station connector</b>	N/A	N/A	N/A
	Other	N/A	N/A	N/A
buil	It-in GPS module	N/A	N/A	N/A
built-in 3/3.5G module		N/A	N/A	N/A
	TPM	-	-	-
Fi	inger Print (FP)	N/A	N/A	N/A
		* Ice Cool Design	* Ice Cool Design	* Ice Cool Design
Additional features		* F9 one key recovery	* Power 4 Gear Hybrid	* Power 4 Gear Hybrid
		* Power 4 Gear Hybrid	* Chocolate Keyboard with Numeric Keys	* Chocolate Keyboard with Numeric Keys
AC power adapter		Output: 19V DC, 3.42A, 65W	2 Output: 19V DC, 3.42A, 90W(TBD)	2 Output : 19V DC, 4.74A, 90W
		☑ Input: 100~240V AC, 50/60Hz universal Output	☑ Input: 100~240V AC, 50/60Hz universal Output	Input : 100~240V AC, 50/60Hz universal
		2 3/2 pin compact power supply system	② 3/2 pin compact power supply system	2 2/3 pin power supply system
D-W-		* Standard: Li- Ion 18650 x 6 cell 3S2P, 2200mAh (4 hrs	, , , , , , , , , , , , , , , , , , , ,	② Li-lon 6cell battery pack
Battery		battery life under average usage scenario)	2200mAh Cell compatible	2 2200mAh Cell compatible
os		Windows 7 Home Premium 64bit	Windows 7 Home Premium 64bit	Windows 7 Home Premium 64bit
Warranty		2 Years Pick Up and Return Warranty	2 Years Pick Up and Return Warranty	2 Years Pick Up and Return Warranty
Dimensions, cm		* 370(L)X256(W)X31~35.5(H)mm	38.0(W) x 25.5 (D) x 3.57 (H) cm	42.0(W) x 28.1(D) x 3.50~3.74(H) cm
		② <2.6Kg	2.62Kg (6cell)	3.11 Kg (w/6cell)
Weight, kg		□ <2.0Kg	Z.OZNY (OLEII)	o. i i ky (w/ocell)